



## Ready for action

### Consono 35 Mk3

The Consono 35 Mk3 is a 5.1 home cinema set that delivers huge sound from a compact design. Experience movies and music in a whole new dimension with this high-performance system. A sleek design and distortion-free, high-powered sound put the Consono 35 Mk3 in a class of its own.

#### Highlights:

- Sets a new standard for affordability, reliability, and performance
- Visually and acoustically revamped satellites with robust metal grating
- Five identically constructed 2-way loudspeakers for a truly immersive sound experience
- Powerful 250 Watt down-fire subwoofer with a 250mm driver
- Suitable for all AV-receivers

## Included components

- 1 x Centre Speaker CS 35 C Mk3
- 4 x Satellite-Speaker CS 35 FCR Mk3
- 1 x Mono-Subwoofer US 2110/1 SW
- 1 x power cable

## Technical Data

### Mono-Subwoofer US 2110/1 SW:

<b>Speaker</b>	Sensitivity (2.83 V / 1 m) [dB]	88 dB
	Maximum sound pressure level [dB/1m]	114 dB/1m
	Frequency range from/to [Hz]	40 - 250 Hz
	Woofer (number per enclosure)	1
	Woofer (diameter) [mm]	250,00 mm
	Woofer (material)	Zellulose, beschichtet
	Miscellaneous	Per Klippel®-Messverfahren optimierte Tieftöner mit langem Hub
	Acoustic principle	1-Weg
	Enclosure type	Bassreflex, DPU
	Enclosure material	MDF
	Enclosure surface	Folie, Hochglanzlack
	Equalisation openings	1
	Equalisation openings (pos.)	Unten
	Net internal volume [Litres]	45 Liter
	Integrated stand	Yes
	Diameter of the stand screw threads [mm]	6,00 mm
	Magnetic shielding	Yes
	Miscellaneous	Reflexkanal in DPU-Technik vermeidet Strömungsgeräusche Stabiler MDF-Gehäuseaufbau mit Innenverstrebrungen und dekorativen Hochglanzakzenten
	Suitable for AV receiver	Yes
<b>Connections</b>	Cinch input	1
	Miscellaneous	Rückversetzte Endstufe für Aufstellung direkt an der Wand
<b>Electronics</b>	Lowest frequency (-3 dB) [Hz]	38 Hz
	Bass boost/EQ	Ja
	Input gain adjustment	Ja

	Level control	Ja
	Phase control	0 / 180 Grad
	Amplifier technology	Class D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass [W]	150 Watt
	Power output capacity sinus (RMS) Bass [W]	125 Watt
	Miscellaneous	Hochleistungs-Netzteil für potente Stromversorgung
	Power supply voltage [volts]	230 Volt
	Standby-Function	Yes
	Standby-Power consumption [watt]	0,50 Watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Fuse	Ja
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Miscellaneous	Gerät entspricht den CE, RoHS und REACH-Anforderungen
<b>Dimensions</b>	Depth [cm]	34,50 cm
	Width [cm]	34,50 cm
	Height [cm]	55,00 cm
	Weight [kg]	20,30 kg
	Miscellaneous	Resonanzdämpfende GummifüÙe im Lieferumfang enthalten

#### Satellite-Speaker CS 35 FCR Mk3:

<b>Speaker</b>	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	160 Watt
	Sensitivity (2.83 V / 1 m)	88 dB
	Minimum amplifier output power recommended	10 Watt
	Maximum sound pressure level	105 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	150 - 20000 Hz
	Crossover frequency internal switch	3400 Hz
	Crossover frequency to Woofer (recommended)	150 - 180 Hz
	Miscellaneous	Neutral tuning
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	Silk
	Midrange driver (number per enclosure)	2

	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	Cellulose, coated
	Miscellaneous	High excursion drivers
	Acoustic principle	2-way
	Enclosure type	Sealed
	Enclosure material	Synthetic
	Enclosure surface	Impact-resistant lacquer, matte
	Net internal volume	1.20 Litres
	Diameter of the stand screw threads	6.00 mm
	Keyhole plate mounted	Yes
	Miscellaneous	Strong walls minimize resonances
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
	Miscellaneous	requires little power for high levels
<b>Dimensions</b>	Depth	9.50 cm
	Width	10.00 cm
	Height	22.60 cm
	Weight	1.25 kg

#### Centre Speaker CS 35 C Mk3:

<b>Speaker</b>	Continuous power handling (IEC - Long Term)	80 Watt
	Peak power capacity (IEC - Short Term)	160 Watt
	Sensitivity (2.83 V / 1 m)	88 dB
	Minimum amplifier output power recommended	10 Watt
	Maximum sound pressure level	105 dB/1m
	Impedance	4 - 8 Ohm
	Frequency range from/to	150 - 20000 Hz
	Crossover frequency internal switch	3400 Hz
	Crossover frequency to Woofer (recommended)	150 - 180 Hz
	Tweeter (number per enclosure)	1
	Tweeter (diameter)	19.00 mm
	Tweeter (material)	silk
	Midrange driver (number per enclosure)	2
	Midrange driver (diameter)	80.00 mm
	Midrange driver (material)	coated cellulose
	Miscellaneous	high excursion driver
	Acoustic principle	2-way
	Enclosure type	closed
	Enclosure material	structure - synthetic
	Enclosure surface	impact-resistant lacquer, matte

	Net internal volume	1.20 Litres
	Diameter of the stand screw threads	6.00 mm
	Keyhole plate mounted	Yes
	Miscellaneous	strong walls minimize resonances
	Maximum cable diameter	2.50 mm
	Suitable for AV receiver	Yes
	Miscellaneous	requires little power for high levels
<b>Dimensions</b>	Depth	9.50 cm
	Width	22.60 cm
	Height	10.00 cm
	Weight	1.25 kg