



Raising the bar

Cinebar 52 THX

We've raised the bar even higher. Behold the Cinebar 52 THX: A soundbar that sets a new standard for sound, features, and ease-of-use. This compact speaker is so good, it even fulfilled the stringent requirements for THX certification. Better sound from a single system is simply not possible.

Highlights:

- The world's only THX-licensed speaker bar device for authentic cinema playback
- The best-sounding soundbar available: 300 Watt amplifier, 7 drivers, 2-way system
- Powerful 250 Watt subwoofer and 35 Hz frequency limit for THX bass fireworks
- Dolby Virtual speaker technology for surround sound from just one box
- Easy setup and ready-to-play thanks to 4 HDMI inputs with 3D support

Included components

- 1 x Subwoofer CB 52 SW
- 1 x power cable
- 1 x Soundbar Cinebar 52 SB
- 1 x power cable
- 1 x table stand for CB 52 SB
- 1 x wall bracket for CB 52 SB
- 1 x mono cinch cable for Sounbar CB 52 SB
- 1 x Angle bracket adapter HDMI 90° for CB 52 SB
- 1 x Angle bracket adapter HDMI 270° for CB 52 SB
- 2 x Angle bracket adapter cinch 90° for CB 52 SB
- 1 x Angle adapter (rotating) TOSLINK for CB 52 SB
- 1 x remote control for Cinebar 52

Technical Data

Soundbar Cinebar 52:

Speaker	Maximum sound pressure level	103 dB/1m
	Frequency range from/to	120 - 22000 Hz
	Tweeter (number per enclosure)	2
	Tweeter (diameter)	25.00 mm
	Tweeter (material)	Aluminium
	Midrange driver (number per enclosure)	4
	Midrange driver (diameter)	100.00 mm
	Midrange driver (material)	Cellulose, coated
	Acoustic principle	2-way
	Enclosure type	Sealed
	Enclosure material	Aluminium
	Enclosure surface	Brushed aluminium
	Net internal volume	11.30 Litres
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
	Screw hole diameter	4.00 mm
	Magnetic shielding	Yes
Connections	Digital inputs coaxial	2
	Digital inputs optical	2
	Cinch input stereo	1
	Stereo jack 3.5mm - in	1
	Bass driver output	1
	Video inputs- HDMI	4
	HDMI Version	1.4b
	Miscellaneous	3D video support, ARC, CEC

Playback	Dolby Digital	Yes
	DTS	Yes
	Dolby Pro Logic	Yes
	Dolby Pro Logic II	Yes
	Dolby Virtual Speaker	Yes
Electronics	Amplifier technology	Class D
	Amplifier configuration	2.0
	Amplifier channels	2
	Power output capacity impulse (peak) Satellite	150 W
	Power output capacity sinus (RMS) Satellite	100 W
	Power supply voltage	230 volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	400 watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Fuse	1.6 A
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Radio remote control	Yes
	Materials	Aluminium
Wall mounts	Miscellaneous	Integrated wall mount
Dimensions	Depth	10.00 cm
	Width	102.00 cm
	Height	14.00 cm
	Weight	8.60 kg
	Miscellaneous	If placed on the included stand, the Cinebar has a height of 15 cm

Subwoofer CB 52 SW:

Speaker	Maximum sound pressure level	101 dB/1m
	Frequency range from/to	35 - 120 Hz
	Woofer (number per enclosure)	1
	Woofer (diameter)	250.00 mm
	Woofer (material)	Cellulose, coated
	Acoustic principle	1-way
	Enclosure type	Bass reflex
	Enclosure material	MDF
	Enclosure surface	Laminate, matte
	Equalisation openings	2
	Equalisation openings (pos.)	Bottom

	Integrated stand	Yes
	Magnetic shielding	Yes
Connections	Cinch input	1
Electronics	Lowest frequency (-3 dB)	35 Hz
	Level control	Yes
	Amplifier technology	Class-D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass	250 W
	Power output capacity sinus (RMS) Bass	150 W
	Power supply voltage	230 volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Fuse	1,6 A
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
Dimensions	Depth	46.00 cm
	Width	31.00 cm
	Height	42.00 cm
	Weight	17.20 kg