



Three-in-one

Cinebar Trios "3.1-Set"

The Cinebar Trio is a modular system for those who want it all, in as small a format as possible. The complete 3.1 soundbar / subwoofer combination can even be expanded into a 5.1 system with the addition of wireless rear speakers.

Highlights:

- Plug-and-play 3.1 soundbar with flat wireless subwoofer
- Integrated high-performance centre speaker for enhanced speech intelligibility
- Wireless flat subwoofer can be placed under a sofa or even wall-mounted
- 465 Watt 2-way system uses a total of 12 drivers to create powerful and precise sound
- Teufel Dynamore® Technology creates an immersive soundscape

Included components

- 1 x Soundbar CS 42
- 1 x power cable
- 1 x Remote Control CS 42 RC
- 1 x Subwoofer T 4000 SW (without wireless module)
- 1 x SubConnect MOD

Technical Data

Soundbar CS 42:

Speaker	Continuous power handling (IEC - Long Term)	45 Watt
	Peak power capacity (IEC - Short Term)	60 Watt
	Maximum sound pressure level	104 dB/1m
	Frequency range from/to	130 - 20000 Hz
	Tweeter (number per enclosure)	3
	Tweeter (diameter)	20.00 mm
	Tweeter (material)	Silk
	Midrange driver (number per enclosure)	6
	Midrange driver (diameter)	77.00 mm
	Midrange driver (material)	Coated cellulose
	Acoustic principle	2-way system
	Enclosure type	Sealed
	Enclosure material	Aluminium
	Enclosure surface	Brushed aluminium
	Net internal volume	7 Litres
	Integrated stand	Yes
	Wall mounting brackets	Yes
	Keyhole plate mounted	Yes
Connections	NFC	Yes
	Digital inputs optical	1
	Stereo jack 3.5mm - in	1
	Bass driver output	1
	Video inputs- HDMI	1
	Video inputs- HDMI	Yes
	HDMI Version	1.4b
	Video outputs - HDMI	1
	Video outputs - HDMI	Yes
	Miscellaneous	HDMI CEC HDMI ARC 4K passthrough 3D video support
	USB 2.0	per software update

	Bluetooth	Bluetooth 4.0 aptX
Playback	DTS NEO:6	Yes
	Dolby Digital	Yes
	DTS	Yes
Electronics	Dolby Pro Logic	Yes
	Dolby Pro Logic II	Yes
	Amplifier technology	Class D
	Amplifier configuration	3.0
	Amplifier channels	6
	Power output capacity impulse (peak) Satellite	55 W
	Power output capacity sinus (RMS) Satellite	75 W
	Power supply voltage	230 volts
	Standby-Function	Yes
	Standby-Power consumption	0.40 watt
	Maximum power consumption	225 watt
	Safety class	2
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
	Display	Yes
	OSD	Yes
	Integrated DSP	Yes
	Audio-Digital-Analog-Converter	24 Bit/96 kHz Cirrus Logic
	Infrared remote control	Yes
Dimensions	Materials	Aluminium
	Depth	9.80 cm
	Width	115.00 cm
	Height	9.30 cm
	Weight	6.50 kg
	Miscellaneous	Total height with table stand is 11.70 cm

Subwoofer T 4000:

Speaker	Maximum sound pressure level [dB/1m]	102
	Frequency range from/to [Hz]	35-200 Hz
	Woofer (number per enclosure)	3
	Woofer (diameter) [mm]	130
	Woofer (material)	Cellulose, coated
	Miscellaneous	Extreme stroke capability
	Acoustic principle	Bass reflex, DPU
	Enclosure type	Open
	Enclosure material	MDF

	Enclosure surface	Matte lacquer
	Integrated stand	Yes
	Suitable for AV receiver	Yes
Connections	Cinch input stereo	1
Electronics	Lowest frequency (-3 dB) [Hz]	35
	Input gain adjustment	Yes
	Frequency regulator (range) [Hz]	Yes
	Phase control	Yes
	Amplifier technology	Class-D
	Amplifier configuration	1.0
	Amplifier channels	1
	Power output capacity impulse (peak) Bass [W]	240
	Power output capacity sinus (RMS) Bass [W]	150
	Miscellaneous	DSP from analogue devices
	Power supply voltage [volts]	230 Volt
	Standby-Function	Yes
	Standby-Power consumption [watt]	.4
	Mains cable - IEC connector (non-heating device)	Yes
	Safety class	2
	Fuse	Yes
	Storage for settings when disconnected	Yes
	Automatic on/off	Yes
Dimensions	Depth [cm]	30
	Width [cm]	95.5
	Height [cm]	12.5
	Weight [kg]	13.2